





DEALER:

## DEUTZ-FAHR Agrolux 4.80

## **TECHNICAL DATA**

## **AGROLUX 4.80**

ENGINE		1000.4 W
Cylinders/Displacement	no./cm <sup>3</sup>	4 / 4000
Aspiration		Natural
Max. homologated net power	HP/kW	73 / 54
Nominal engine speed	rpm	2350
Max. torque	Nm	270
Cooling		liquid-oil
Engine control		mechanical
Air cleaner		dry type air filter with pre-cleaner
Silencer underhood		with vertical exhaust pipe
Fuel tank capacity	litres	56

DIMENSIONS AND MEIGHTS / W		40.0
DIMENSIONS AND WEIGHTS (with rear tyr	es)	16.9 x 30
Max. length without link arms	mm	3225
Min - max. width	mm	1822/2336
Max. height at engine hood	mm	1355
Max. height at steering wheel	mm	1505
Ground clearance	mm	400
Wheelbase	mm	2105
Front track - max.	mm	1740
Rear track - max.	mm	1800
Minimum steering radius without braking	mm	3700
Weight with safety frame	kg	2820

TRANSMISSION						
Gearbox clutch		mechanically operated				
Mechanical gearbox, 4	synchronised	12 FWD + 3 REV				
gears, 3 gear range						
Max. speed	km/h	30				
Shuttle		reverse shuttle mechanical				
Rear differential lock		mechanically operated				
Lubrication		forced				
BRAKES AND STEERIN	NG .					
Braking system		discs in oil bath on rear tyres, hydrostatically operated				
Parking brake		independent				
Steering		mechanical				
		hydrostatic				
Steering angle	4WD	55°				
Pump delivery		l/min. 17 litres				

FRONT AXLE					
Drive engagement	mechanically operated				
Front differential lock	mechanically operated				
REAR P.T.O.					
Clutch	dry type				
Speed rpm	540				
Operation	mechanical, independent				
HYDRAULIC LIFT					
Rear power lift	mechanical				
Maximum lifting capacity kg	3000				
Pump delivery I/min.	45				
Auxiliary hydraulic control valveswa					
3 point linkage (link arms and top li	nk)				
fixed hitching balls					
RH link arm and stabilisers	mechanical				
DRIVING POSITION					
Gears levers	lateral				
Protection	2 post fixed rops				
Instruments	analog				
Driver's seat	mechanical adjustment				

12 FWD + 3 REV - SPEED IN KPM AT AN ENGINE SPEED OF 2350 RPM WITH 14.9 X 28 REAR TYRES											
1L	2L	3L	4L	1M	2M	3M	4M	1V	2V	3V	4V

For exact specifications please consult your local Deutz-Fahr dealer. The above specifications refer to tractors with all available equipment. For standard equipment and options, refer to the current price list and ask your local dealer for details.



P+61 (03) 8353 3600 F+61 (03) 8353 3699

**W** www.deutztractors.com.au

199 Australis Drive, Derrimut Victoria 3030

