

## AGROTRON TTV 9340

### Engine

Deutz TTCD 7.8 LO6 Tier 4 Final Diesel Engine  
 6 Cyl/7775cc Double Stage Turbocharged / Inter-cooled  
 Electronically Controlled  
 4 Valves Per Cylinder  
 SCR (Selective Catalytic Reduction), EGR (External Catalytic Reduction) and DPF (Diesel Particulate Filter)  
 Liquid/Oil Cooled  
 Common Rail DCR Injection System  
 316 Rated Hp @ 2100 rpm (2000/25/CE)  
 336 Max Hp @1900 rpm  
 Constant Power Range 1600-1200 rpm  
 Torque 1372 Nm @ 1600 rpm  
 100% Bio Diesel Compliant  
 Engine Speed Programming (x2 Speeds)  
 Powercore Air Filter with Dust Ejectors  
 Side Vertical Exhaust  
 600 Lt Fuel Capacity /65 litre Ad-Blue Capacity  
 Electronically Controlled Front Bonnet (Open and Close) + Manual Control

### Transmission

ZF Terramatic TMT 32 TTV Transmission  
 4 Working Ranges  
 3 Driving Modes (Auto, PTO, Manual)  
 Acceleration and Power Adjustment  
 Speed Cruise Control x2  
 Active Stationary Control  
 Electronic Park Brake  
 Wet Clutch Powershuttle  
 Sense Clutch with 5 Power Shuttle Settings  
 Four Wheel Drive (FWD)- Elec/Hyd Engagement  
 Front & Rear Diff Lock-100%  
 ASM Auto Diff Lock and 4wd Engagement  
 Separate Transmission Fluid Reservoir  
 50 km/h Road speed @1480rpm

### Wheel Equipment

650-65-R34 Front 710-75-R42 Rear  
 Fixed Centres  
 Michelin Brand



### Braking & Front Axle

Dana 770 Front Axle  
 Front Axle Suspension With 90 MM Travel total  
 50 Degree Steering Angle  
 Front Externally Mounted Dry Disc Brakes (50% Brake Force)  
 "Power Brake System" Brake Booster System  
 Hydraulic Trailer Braking  
 Pneumatic Trailer Braking  
 20 Litre Additional Air Tank For Pneumatic Trailer Braking System

### Hyd/Linkage

Load Sensing Hyd Pump System  
 160 L/min Hyd Flow at Rear Remotes  
 Steering Pump-Separate — 44 litres/Min  
 Power Beyond Valve  
 Separate Hydraulic Fluid Reservoir (80 Litres)  
 7 Sets of Electro-Hyd Remotes (5 rear/2 front)  
 Flow Control and Timer on all Remotes  
 AGROTRONIC EHR with Position & Draft Control  
 Free Flow Return Line  
 Implement Ride Control  
 External Raise & Lower on Rear Fenders  
 Cat III Hook Ends-Telescopic Automatic Stabilisers  
 12000 kg lift Capacity-with Assistor Rams  
 Rear Trailer Hitch D.38 With Pin .80 MM + Forced Steering Ball  
 Front Linkage (5,000 kg) and PTO System  
 Comfort Pack-Front Hydraulic Kit  
 Ground Controls For Front Lift  
 Electrical Socket Integrated Into Front Lift

## AGROTRON TTV 9340

### Operator Environment

NEW Maxi Vision 2 Cabin  
 Automatic Climate Air Conditioning  
 New Panorama Front Window  
 Tinted Side and Rear Glass  
 Hi Visibility Glass Roof Hatch with Sun Grill  
 Self Levelling Pneumatic Cabin Suspension  
 Seat-Max Dynamic XXL Super Deluxe Air Seat  
 Seat Rear Headrest  
 INFOCENTER III Digital Display  
 COMFORTIP Headland Management System  
 Powercom Control Lever  
 Leather and Fabric Trainee Seat with Seatbelt  
 Refrigerated and Heated Drinks Storage Compartment  
 I Monitor 2-12 Inch Touch Screen Display  
 A Post Colour Display  
 Audio system (Bluetooth+MP3+Radio) with Quad Speakers  
 Single Rear Colour Video Camera  
 WOLP Lighting Package  
 Telescopic Mirrors- Heated and Electric  
 Rear ISOBUS Connection (ISO 11783)  
 7 pin Socket for Implements (ISO 11786)  
 "Easy Steer" Adjustable Steering System  
 AGROSKY GPS Ready—Requires AGI-4 Receiver

### PTO

Independent Wet Multidisc Clutch  
 3 Speed PTO 540E/1000/1000E  
 Modulated PTO Engagement  
 Internal PTO Brake  
 Auto PTO  
 External PTO Start/Stop  
 Interchangeable PTO Spline Function  
 1 3/4 Inch Shaft with 20 Splines Supplied  
 1 3/8 Inch Shaft with 21 Splines Supplied  
 1000 Eco Speed Front PTO



### Miscellaneous

Rear Fender Extensions  
 PTO, Linkage and Rear Hydraulic Controls Located on Both Rear Guards  
 Dynamic Front Fenders  
 Toolbox  
 Radar  
 Courtesy Lights For illuminating Entrance to Cabin  
 4 Front and 4 Rear Roof Mounted Work Lights  
 2 Front LED Work Lights (Bonnet)  
 2 Additional Front Low Work Lights  
 2 Additional Rear Low Work Lights  
 2 Additional Front Lights On Cabin Post (FL and PTO)  
 Additional Rear Work Light on Mudguard  
 Rotary Beacon

### Weights & Dimensions

47% - 53% Front to Rear Weight Distribution  
 Wheelbase 3135 mm  
 Length 5268 mm  
 Total Height 3500mm  
 Length 5268 mm  
 Total Unladen Weight 12,000 kg  
 Max Permissible Total Weight 18,000 kg

Power Farming reserves the right to change standard equipment at any time without prior notice

Revised January 2016